

## CSP Commercial Service Pedestal

- 16" Wide, 48" High, 16.25" Deep
- Double door design with swing side top section
- Hinged viewing window for easy programming
- All access points include padlock provisions
- Caltrans Type III-BF & ES-2E Compliant
- EUSERC 308 Compliant
- NEMA TYPE 3R Rated UL 508A Listed
- Metered and Unmetered Available
- Anchor bolts included
- 5 Year Limited Warranty

### METER SECTION

- Meter Socket: 4 Jaw, 100 or 200 Amp
- 120v, 208v and 240v models available
- Meter Socket with Test Blocks
- Utility Landing Lugs: 200 Amp

### CUSTOMER SECTION

- 11" x 14" customer usable area
- 100 and 200 amp load centers with up to 16 circuits



### SPECIFICATIONS ON PAGE 48

### CSP Standard Model Numbers

Model No	Main Amps	Voltage	Phase	Jaw	Wires	AIC Rating	Breaker Positions
CSP-11008-10	100	120/240	1	4	3	10,000	8
CSP-11008-22	100	120/240	1	4	3	22,000	8
CSP-11008-65	100	120/240	1	4	3	65,000	8
CSP-11016-10	100	120/240	1	4	3	10,000	16
CSP-11016-22	100	120/240	1	4	3	22,000	16
CSP-11016-65	100	120/240	1	4	3	65,000	16
CSP-12016-10	200	120/240	1	4	3	10,000	16
CSP-12016-22	200	120/240	1	4	3	22,000	16
CSP-12016-65	200	120/240	1	4	3	65,000	16

T-Fuse available on select models. No-distribution options available upon request.

SERIES: MPS 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION 26 POSITION	
	125A		
	150A		
	175A		
200A			
AIC RATING			
10,000	22,000	65,000	

Load center with no distribution also available. Contact factory for details about all non-standard configurations.

SERIES: MPS 3 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	18 POSITION 24 POSITION	
	125A		
	150A		
	175A		
200A			
AIC RATING			
10,000	22,000	65,000	

Load center with no distribution also available. Contact factory for details about all non-standard configurations.

SERIES: CSP 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION	
	125A		
	150A		
	175A		
200A			
AIC RATING			
10,000	22,000	65,000	

Load center with no distribution also available. Contact factory for details about all non-standard configurations.

SERIES: DSP 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION	
		16 POSITION	
	AIC RATING		
	10,000	22,000	65,000

Load center with no distribution also available. Contact factory for details about all non-standard configurations.