

MPS Meter Pedestal

- 18" Wide, 52" High, 20" Deep
- Double door design with swing side top section
- Hinged viewing window for easy programming
- All access points include padlock provisions
- EUSERC 308 Compliant
- NEMA TYPE 3R Rated UL 508A Listed
- Anchor bolts included for installation
- 10 Year Limited Warranty

METER SECTION

- Meter Socket: 4 or 7 Jaw; 100 or 200 Amp Available
- 120v, 208v and 240v Models Available

CUSTOMER SECTION

- Up to 21" x 7" customer usable area
- 100-200 amp load centers with up to 26 circuits

SPECIFICATIONS ON PAGE 46



MPE Meter Pedestal with Enclosure SB-1852SS

- 18" Wide, 52" High, 32" Deep
- Upgrade any MPS Model No. to an MPE
- Maximum storage with attached enclosure
- EUSERC 308 Compliant
- NEMA TYPE 3R Rated UL 508A Listed
- 10 Year Limited Warranty

ENCLOSURE SECTION

- Enclosure SB-1852SS addition (See Page 4)
- Removable backboard for mounting components
- Large door-mounted storage area
- Cross flow side louvers for ventilation

SPECIFICATIONS ON PAGE 47



MPS Standard Model Numbers

	Model No	Main Amps	Voltage	Phase	Jaw	Wires	AIC Rating	Breaker Positions
1 PHASE	MPS-11016-10	100	120/240	1	4	3	10,000	16
	MPS-11016-22	100	120/240	1	4	3	22,000	16
	MPS-11016-65	100	120/240	1	4	3	65,000	16
	MPS-11026-65	100	120/240	1	4	3	65,000	26
	MPS-11226-22	125	120/240	1	4	3	22,000	26
	MPS-11226-65	125	120/240	1	4	3	65,000	26
	MPS-11526-22	150	120/240	1	4	3	22,000	26
	MPS-11526-65	150	120/240	1	4	3	65,000	26
	MPS-12016-22	200	120/240	1	4	3	22,000	16
	MPS-12016-65	200	120/240	1	4	3	65,000	16
	MPS-12026-22	200	120/240	1	4	3	22,000	26
	MPS-12026-65	200	120/240	1	4	3	65,000	26
3 PHASE	MPS-31018-10	100	120/208	3	7	4	10,000	18
	MPS-31018-22	100	120/208	3	7	4	22,000	18
	MPS-31018-65	100	120/208	3	7	4	65,000	18
	MPS-32024-10	200	120/208	3	7	4	10,000	18
	MPS-32024-22	200	120/208	3	7	4	22,000	24
	MPS-32024-65	200	120/208	3	7	4	65,000	24

T-Fuse available on select models. No-distribution options available upon request.

SERIES: MPS 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION 26 POSITION	
	125A		
	150A		
	175A		
200A			
AIC RATING			
10,000	22,000	65,000	

Load center with no distribution also available. Contact factory for details about all non-standard configurations.

SERIES: MPS 3 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	18 POSITION 24 POSITION	
	125A		
	150A		
	175A		
200A			
AIC RATING			
10,000	22,000	65,000	

Load center with no distribution also available. Contact factory for details about all non-standard configurations.

SERIES: CSP 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION	
	125A		
	150A		
	175A		
200A			
AIC RATING			
10,000	22,000	65,000	

Load center with no distribution also available. Contact factory for details about all non-standard configurations.

SERIES: DSP 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION	
		16 POSITION	
	AIC RATING		
	10,000	22,000	65,000

Load center with no distribution also available. Contact factory for details about all non-standard configurations.