

**PWP
Power Pedestal**

- 17" Wide, 31" High, 17" Deep
- 100% Stainless Steel
- All access points include padlock provisions
- NEMA TYPE 3R Rated and UL 508A Listed
- Anchor bolts included for installation
- 10 Year Limited Warranty

CUSTOMER SECTION

- Up to 21" x 7" customer usable area
- 100-200 amp load centers with up to 16 circuits



PWP Standard Model Numbers

Model No	Main Amps	Voltage	Phase	Jaw	Wires	AIC Rating	Breaker Positions
PWP-11016-10	100	120/240	1	4	3	10,000	16
PWP-11016-22	100	120/240	1	4	3	22,000	16
PWP-11016-65	100	120/240	1	4	3	65,000	16
PWP-12016-22	200	120/240	1	4	3	22,000	16
PWP-12016-65	200	120/240	1	4	3	65,000	16

SERIES: MPS 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION 26 POSITION	
	125A		
	150A		
	175A		
	200A		
AIC RATING			
10,000	22,000	65,000	

SERIES: MPS 3 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	18 POSITION 24 POSITION	
	125A		
	150A		
	175A		
	200A		
AIC RATING			
10,000	22,000	65,000	

SERIES: CSP 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION	
	125A		
	150A		
	175A		
	200A		
AIC RATING			
10,000	22,000	65,000	

SERIES: DSP 1 PHASE	OPTIONS AVAILABLE		
	AMPERAGE	LOAD CENTER	
	100A	8 POSITION 16 POSITION	
AIC RATING			
10,000	22,000	65,000	

SERIES: PWP 1 PHASE	OPTIONS AVAILABLE	
	AMPERAGE	LOAD CENTER
	100A	8 POSITION
	200A	16 POSITION
	AIC RATING	
10,000	22,000 65,000	

*Load center with no distribution also available. Contact factory for details about all non-standard configurations.