

## DSP Dual Service Pedestal

- 26" Wide, 50" High, 17.25" Deep
- Double door design with lift-up top section
- Hinged viewing window for easy programming
- All access points include padlock provisions
- Caltrans Type III-CF compliant
- EUSERC 308A Compliant
- NEMA TYPE 3R Rated UL 508A Listed
- Metered and Unmetered Available
- Anchor bolts included
- 10 Year Limited Warranty

### METER SECTION

- Meter Socket: 4 Jaw, 100 Amp
- 120 or 240v models available
- Meter Socket with Test Blocks
- Utility Landing Lugs: 200 Amps

### CUSTOMER SECTION

- 11" x 14" customer usable area
- 100-200 amp load centers
- 8 circuits (per meter)



### SPECIFICATIONS ON PAGE 50

### DSP Standard Model Numbers

Model No	Main Amps	Voltage	Phase	Jaw	Wires	AIC Rating	Breaker Positions
DSP-11008-10	100A   100A	120/240	1	4	3	10,000	8   8
DSP-11008-22	100A   100A	120/240	1	4	3	22,000	8   8
DSP-11008-65	100A   100A	120/240	1	4	3	65,000	8   8
DSP-12008-10	200A   200A	120/240	1	4	3	10,000	8   8
DSP-12008-22	200A   200A	120/240	1	4	3	22,000	8   8
DSP-12008-65	200A   200A	120/240	1	4	3	65,000	8   8

T-Fuse available on select models. No-distribution options available upon request.